Range of accessories for Device testers TG omni 1 & 2 TG basic 2 & 2+





- · Tablet 8"
- · Bluetooth-Keyboard
- · RFID-Reader
- ·Three-phase adapter
- · Measuring accessories-set
- · Brush probe
- · Label printer



Tablet 8"

Included original protective cover



Tablet 8 "Samsung Galaxy, black, Android 5.1, available internal memory approx. 4.3 GB, memory expansion mini-SD up to 200 GB, WLAN 802.11 b / g / n 2.4 GHz, incl. charger, original Samsung protective cover and pre-installed apps, pre-configured ready for use

Tablet 8" incl.

Original protective cover

- TG omni 1 App
- Barcode-Scanner-App
- Adobe Acrobate

External Bluetooth Keyboard

Bluetooth-Keyboard

External

External stand-alone Bluetooth keyboard, color black, 80/81 keys, QWERTZ, Bluetooth 3.0,

RFID-Reader

125 kHz + 13,56 MHz



• USB-Connection cable 2,0 m

USB-RFID-Reader Equipment:

• HID-Emulation (USB-Keyboard)

Dimensions (B x H x T) ca. 290 x 128 x 13mm

- Range up to 100 mm
- Frequency: 125 kHz und 13,56 MHz / ISO 14443A+B+NFC / ISO 15693
- Dimensions: 88 x 56 18 mm
- incl. OTG-Adapter USB 2.0 Socket-A to micro-USB plug-B

RFID-Reader

Order-No.: 7920019220

Order-No.: 7920019003

Order-No.: 7920019300

Measuring accessories-set





Measuring accessories-set, red, consisting of:

- 1 x Test lead with Test tip
- 1 x Alligator clip

Test lead length 2,0 m Test lead length 3,0 m Order-No.: 7920019020 Order-No.: 7920019025

Measuring accessories-set

Measuring accessories-set, for tests on arc welding devices, consisting of:

ARC

- 1 x 2,0 m test lead with yellow test tip
- 1 x 2,0 m test lead with blue test tip
- 1 x Alligator clip yellow
- 1 x Alligator clip blue

ARC measurement accessories-set

Order-No.: 7920019210



Three-phase adapter sets

for three-phase consumers and CEE extension cables





For testing three-phase consumers and CEE-extension cables. Measurement of the leakage current using the differential current measurement me tion current with the three-phase adapter TCEE (5-pin CEE plug to 5-pin CEE couplin insulated Individual cables and the residual current clamp TGSZ 40. Measurement functions: • Measurement of the residual current across all active conductors L1-L2-L3-N (TCE • Measurement of the consumer in Phases L1-L2-L3 (TCEE) • Functional test (TCEE) • Measurement of the protective conductor resistance (VLCEE) • Measurement of insulation resistance (VLCEE) • Wiring test (VLCEE) • Phase order (VLCEE)	g, reinforced (double)
Three-phase adapter-set for 16 A und 32 A VLCEE 16 A, VLCEE 32 A, TCEE 16 A, TCEE 32 A, Residual current clamp TGSZ 40	Order-No.: 7920019200

Three-phase adapter-set for 16 A VLCEE 16 A, TCEE 16 A, residual current clamp TGSZ 40	Order-No: 7920019180
Three-phase adapter-set for 32 A VLCEE 32 A, TCEE 32 A, Residual current Clamp TGSZ 40	Order-No.: 7920019190
Extension-set VLCEE 16 A + TCEE 16 A	Order-No.: 7920019160
Extension-set VLCEE 32 A + TCEE 32 A	Order-No.: 7920019170
Residual current clamp TGSZ 40 individually	Order-No: 7920019010

Residual current clamp TGSZ 40 individually Measuring range 0,1 mA ... 40 A Frequency range 50 ... 5000 Hz

VLCEE Three-phase adapter

for CEE extension cables



For measuring protective conductor and insulation resistance on three-phase extension cables, consisting of:

5-pin CEE-Plug to PE-4 mm Socket an 5-pin CEE connector to Schuko Plug Measurement functions:

- Measurement of the protective conductor resistance
- Measurement of the insulation resistance
- Wiring test
- Phase order

Three-phase adapter VLCEE 16 A Three-phase adapter VLCEE 32 A Three-phase adapter VLCEE 63 A Order-No.: 7920019030 Order-No.: 7920019040 Order-No.: 7920019140

Passive Three-phase Adapter

for u.a. RCD-Tests in CEE-extension Cables



Passive three-phase Adapter, CEE-Coupling 5/16 A, 5/32 A, 3/16 A to Schuko-Plug Measurement functions:

- Protective conductor resistance
- Insulation resistance per phase L1, L2, L3 against PE und L1+L2+L3 against PE
- RCD-Test in e.g. construction power distributors or CEE-extension cables

Three-phase adapter TGP

Order-No.: 7920018690



Three-phase ad	apter active TGA 16 / 32 A	
	Active three-phase adapter, CEE-Plug/Coupling 5-polig: Measurement functions: • Protective conductor resistance • Insulation resistance • Leakage current according to the residual current mea • Function test	asuring method
	Three-phase adapter TGA 16 A Three-phase adapter TGA 32 A	Order-No.: 792001869 Order-No.: 792001869
Brush probe	Brass	
Brush probe made of brass for tests on rotating or vibrating conductive parts Tests on arc welding equipment (2 pieces required)		ng conductive parts as well as for
1 il fel fel lamon	Brush probe	Order-No.: 7921008604
Label printer USB / WLAN		
	Portable label printer, print resolution up to 600 dpi, USB a app for Android and iOS, up to 200 labels / min, Integrated cutting unit for endless label tapes, with white Label printer	
	Label Printer	Order-No.: 152999122
Omni-Remote	Data management software fo	or Windows® PC
	The PC Software offers the following functions:	
Internet GoogleDrive / VPN	 Online-Synchronization of test Data from seven The data from tablets is added to the data in the Before the synchronization, a backup of the data end test. Presentation of the master data, test data and test. Compilation of checklists with the help of filter. Printout of test reports with all saved results. 	database on a PC. base is automatically created on the tablets. t procedures in tabular form .

Save all test data in a SQLite3-Database. The data can be called up at any time recordable.
Data-Import/Export to other computers in the form of MS Excel® tables.

Omni-Remote with basic license for 1 tester

Expansion license for 1 additional tester

Order-No.: 7920019130 Order-No.: 7920019135

