




## ASRD 205.37 Three-phase current transformer set

Three-phase current transformer set, for primary nominal currents from 3 x 50 A up to 3 x 750 A, secondary nominal current 5 A, 2 A or 1 A, accuracy classes 0.2, 0.5s, 0.5 and 1.



### Dimensions:

Bus bar 1: 20 x 5 mm  
Round conductor: 18 mm  
Width: 115 mm  
Height: 65 mm  
Depth: 37 mm



### Technical details:

Therm. nominal continuous current  $I_{cth}$ : 1,0 x  $I_N$   
Therm. nominal short-time current  $I_{th}$ : 60 x  $I_N$ , 1 sec.

Max. operating voltage  $U_m$ : 0.72 kV  
Isolation test voltage: 3 kV,  $U_{eff}$ , 50 Hz, 1 min.  
Nominal rated frequency: 50 Hz  
Isolation class: E

### Further information:

Over-current limiting factor: See rating plate  
Working temperature range:  $-5^{\circ}\text{C} < T < +40^{\circ}\text{C}$   
Storage temperature range:  
Unbreakable plastic housing made of black polycarbonate:  
Flame resistant, ultrasonically welded  
Nickel-plated secondary terminals with plus-minus nickel-plated screws:  
M5x10 mm  
Secondary caps: integrated  
Package quantity: 1 pcs.  
Custom tariff number: 85043129

### GMW Contact:

[www.g-mw.de](http://www.g-mw.de)  
[info@g-mw.de](mailto:info@g-mw.de)

Phone: +49/9103 7129-0  
Fax: +49/9103 7129-205/207