






SASK 31.5

Protection plug-in current transformer

Bus bar 1 30 x 10 mm
 Bus bar 2 2 x 20 x 10 mm
 Round conductor 28 mm
 Transformer width 61 mm
 Height 75,5 mm
 Depth 68 mm



Primary current [A]	Burden [VA]	Secondary current [A] / Class			
		5 A Cl. 5P5 Art.-no.	5 A Cl. 10P5 Art.-no.	1 A Cl. 5P5 Art.-no.	1 A Cl. 10P5 Art.-no.
75	1			100S17-1116B	100S17-1117B
80	1			100S17-1216B	100S17-1217B
100	1	100S17-1306B	100S17-1307B		
	1,5			100S17-1316C	100S17-1317C
125	1	100S17-1506B	100S17-1507B		
	1,5		100S17-1507C	100S17-1516C	100S17-1517C
150	1	100S17-1606B	100S17-1607B		
	1,5	100S17-1606C	100S17-1607C	100S17-1616C	100S17-1617C
200	1	100S17-1706B	100S17-1707B		
	1,5	100S17-1706C	100S17-1707C	100S17-1716C	100S17-1717C
	2,5	100S17-1706D	100S17-1707D	100S17-1716D	100S17-1717D
250	1,5	100S17-1806C	100S17-1807C	100S17-1816C	100S17-1817C
	2,5	100S17-1806D	100S17-1807D	100S17-1816D	100S17-1817D
300	1,5	100S17-1906C	100S17-1907C	100S17-1916C	100S17-1917C
	2,5	100S17-1906D	100S17-1907D	100S17-1916D	100S17-1917D
400	1,5	100S17-2006C	100S17-2007C	100S17-2016C	100S17-2017C
	2,5	100S17-2006D	100S17-2007D	100S17-2016D	100S17-2017D
500	1,5	100S17-2106C	100S17-2107C	100S17-2116C	100S17-2117C
	2,5	100S17-2106D	100S17-2107D	100S17-2116D	100S17-2117D
600	1,5	100S17-2206C	100S17-2207C	100S17-2216C	100S17-2217C
	2,5	100S17-2206D	100S17-2207D	100S17-2216D	100S17-2217D
750	1,5	100S17-2306C	100S17-2307C	100S17-2316C	100S17-2317C
	2,5	100S17-2306D	100S17-2307D	100S17-2316D	100S17-2317D

		Art.-no.
	Snap-on mounting, type C	10055011
	Sealed shutter, type B	10059041