




SASK 41.4

Protection plug-in current transformer



Bus bar 1 40 x 10 mm
 Bus bar 2 2 x 30 x 5 mm
 Round conductor 32 mm
 Transformer width 71 mm
 Height 85,5 mm
 Depth 58 mm



Primary current [A]	Burden [VA]	Secondary current [A] / Class			
		5 A Cl. 5P5 Art.-no.	5 A Cl. 10P5 Art.-no.	1 A Cl. 5P5 Art.-no.	1 A Cl. 10P5 Art.-no.
100	1	100S24-1306B	100S24-1307B	100S24-1316B	100S24-1317B
120	1	100S24-1406B	100S24-1407B	100S24-1416B	100S24-1417B
125	1	100S24-1506B	100S24-1507B	100S24-1516B	100S24-1517B
150	1	100S24-1606B	100S24-1607B		
	1,5		100S24-1607C	100S24-1616C	100S24-1617C
200	1,5	100S24-1706C	100S24-1707C	100S24-1716C	100S24-1717C
	1,5	100S24-1806C	100S24-1807C	100S24-1816C	100S24-1817C
250	2,5		100S24-1807D	100S24-1816D	100S24-1817D
	1,5	100S24-1906C	100S24-1907C	100S24-1916C	100S24-1917C
300	2,5	100S24-1906D	100S24-1907D	100S24-1916D	100S24-1917D
	1,5	100S24-2006C	100S24-2007C	100S24-2016C	100S24-2017C
400	2,5	100S24-2006D	100S24-2007D	100S24-2016D	100S24-2017D
	1,5	100S24-2106C	100S24-2107C	100S24-2116C	100S24-2117C
500	2,5			100S24-2116D	100S24-2117D
	1,5	100S24-2206C	100S24-2207C	100S24-2216C	100S24-2217C
600	2,5			100S24-2216D	100S24-2217D
	1,5	100S24-2306C	100S24-2307C	100S24-2316C	100S24-2317C
750	2,5		100S24-2307D	100S24-2316D	100S24-2317D

		Art.-no.
	Snap-on mounting, type D	10055012
	Sealed shutter, type B	10059041