




SASK 421.4

Protection plug-in current transformer



Bus bar 1 20 x 10 mm
 Round conductor 20 mm
 Transformer width 71 mm
 Height 85,5 mm
 Depth 58 mm



Primary current [A]	Burden [VA]	Secondary current [A] / Class			
		5 A Cl. 5P5 Art.-no.	5 A Cl. 10P5 Art.-no.	1 A Cl. 5P5 Art.-no.	1 A Cl. 10P5 Art.-no.
100	2,5	100S23-1306D	100S23-1307D	100S23-1316D	100S23-1317D
150	2,5	100S23-1606D	100S23-1607D	100S23-1616D	100S23-1617D
200	1,5	100S23-1706C	100S23-1707C	100S23-1716C	100S23-1717C
	2,5	100S23-1706D	100S23-1707D	100S23-1716D	100S23-1717D
250	1,5	100S23-1806C	100S23-1807C	100S23-1816C	100S23-1817C
	2,5	100S23-1806D	100S23-1807D	100S23-1816D	100S23-1817D
300	1,5	100S23-1906C	100S23-1907C	100S23-1916C	100S23-1917C
	2,5	100S23-1906D	100S23-1907D	100S23-1916D	100S23-1917D
400	1,5	100S23-2006C	100S23-2007C	100S23-2016C	100S23-2017C
	2,5	100S23-2006D	100S23-2007D	100S23-2016D	100S23-2017D

		Art.-no.
	Snap-on mounting	-
	Sealed shutter, type B	10059041