




## SASK 51.4



### Protection plug-in current transformer



Bus bar 1            50 x 12 mm  
 Bus bar 2            2 x 40 x 10 mm  
 Round conductor    44 mm  
 Transformer width   86 mm  
 Height                98,5 mm  
 Depth                 58 mm



Primary current [A]	Burden [VA]	Secondary current [A] / Class			
		5 A Cl. 5P5 Art.-no.	5 A Cl. 10P5 Art.-no.	1 A Cl. 5P5 Art.-no.	1 A Cl. 10P5 Art.-no.
150	1			100S34-1616B	100S34-1617B
200	1	100S34-1706B	100S34-1707B	100S34-1716B	100S34-1717B
	1,5		100S34-1707C	100S34-1716C	100S34-1717C
250	1,5	100S34-1806C	100S34-1807C	100S34-1816C	100S34-1817C
	2,5				100S34-1817D
300	1,5	100S34-1906C	100S34-1907C	100S34-1916C	100S34-1917C
	2,5			100S34-1916D	100S34-1917D
400	1,5	100S34-2006C	100S34-2007C	100S34-2016C	100S34-2017C
	2,5		100S34-2007D	100S34-2016D	100S34-2017D
500	1,5	100S34-2106C	100S34-2107C	100S34-2116C	100S34-2117C
	2,5		100S34-2107D	100S34-2116D	100S34-2117D
600	1,5	100S34-2206C	100S34-2207C	100S34-2216C	100S34-2217C
	2,5		100S34-2207D	100S34-2216D	100S34-2217D
750	1,5	100S34-2306C	100S34-2307C	100S34-2316C	100S34-2317C
	2,5	100S34-2306D	100S34-2307D	100S34-2316D	100S34-2317D
1000	1,5	100S34-2506C	100S34-2507C	100S34-2516C	100S34-2517C
	2,5	100S34-2506D	100S34-2507D	100S34-2516D	100S34-2517D

		Art.-no.
	<b>Snap-on mounting</b>	-
	<b>Sealed shutter, type C</b>	<b>10059042</b>