






## SASK 63.6

Protection plug-in current transformer

Bus bar 1            60 x 30 mm  
 Round conductor    30 mm  
 Transformer width   88 mm  
 Height                129 mm  
 Depth                 78 mm



| Primary current [A] | Burden [VA] | Secondary current [A] / Class |                             |                            |                             |
|---------------------|-------------|-------------------------------|-----------------------------|----------------------------|-----------------------------|
|                     |             | 5 A<br>Cl. 5P5<br>Art.-no.    | 5 A<br>Cl. 10P5<br>Art.-no. | 1 A<br>Cl. 5P5<br>Art.-no. | 1 A<br>Cl. 10P5<br>Art.-no. |
| 200                 | 1,5         | 100S46-1706C                  | 100S46-1707C                | 100S46-1716C               | 100S46-1717C                |
|                     | 2,5         |                               | 100S46-1707D                | 100S46-1716D               | 100S46-1717D                |
| 250                 | 1,5         | 100S46-1806C                  | 100S46-1807C                | 100S46-1816C               | 100S46-1817C                |
|                     | 2,5         | 100S46-1806D                  | 100S46-1807D                | 100S46-1816D               | 100S46-1817D                |
| 300                 | 1,5         | 100S46-1906C                  | 100S46-1907C                | 100S46-1916C               | 100S46-1917C                |
|                     | 2,5         | 100S46-1906D                  | 100S46-1907D                | 100S46-1916D               | 100S46-1917D                |
| 400                 | 2,5         | 100S46-2006D                  | 100S46-2007D                | 100S46-2016D               | 100S46-2017D                |
|                     | 5           |                               | 100S46-2007F                | 100S46-2016F               | 100S46-2017F                |
| 500                 | 2,5         | 100S46-2106D                  | 100S46-2107D                | 100S46-2116D               | 100S46-2117D                |
|                     | 5           | 100S46-2106F                  | 100S46-2107F                | 100S46-2116F               | 100S46-2117F                |
| 600                 | 2,5         | 100S46-2206D                  | 100S46-2207D                | 100S46-2216D               | 100S46-2217D                |
|                     | 5           | 100S46-2206F                  | 100S46-2207F                | 100S46-2216F               | 100S46-2217F                |
| 750                 | 2,5         | 100S46-2306D                  | 100S46-2307D                | 100S46-2316D               | 100S46-2317D                |
|                     | 5           | 100S46-2306F                  | 100S46-2307F                | 100S46-2316F               | 100S46-2317F                |
| 1000                | 2,5         | 100S46-2506D                  | 100S46-2507D                | 100S46-2516D               | 100S46-2517D                |
|                     | 5           | 100S46-2506F                  | 100S46-2507F                | 100S46-2516F               | 100S46-2517F                |

|  |                               | Art.-no.        |
|--|-------------------------------|-----------------|
|  | <b>Snap-on mounting</b>       | -               |
|  | <b>Sealed shutter, type C</b> | <b>10059042</b> |